

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR302-16S2-P16

Uniview



Features

- Uniview
- NVR for IP cameras
- Easy range
- 16 CH
- 160 Mbps bandwidth supported
- Maximum resolution 8 Megapixel
- Compression Ultra265/H.265/H.264
- ONVIF Compatible
- Alarms
- VGA and HDMI 4K output
- Mouse
- Space for 2 HDD up to 10 TB - 16 PoE ports IEEE802.3af/at
- WEB, CMS, Smartphone and NVR interface

Specifications

Brand	Uniview
Range	Easy
Inputs for IP cameras	LAN port up to 16 channels
Power over Ethernet	16 port PoE Switch IEEE802.3af/at (max. 240 W)
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra H.265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200 1280x1024, 1280x720, 1024x768
Total bandwidth	160 Mbps downstream / 64 Mbps upstream
Main Stream recording	8Mpx / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080p / 960p / 720p / D1 / 2CIF / CIF
Alarms	4 inputs / 1 relay
Recording method	Manual, programmed, motion detection
Intelligent functions	People Counting, Face Detection, Intrusion Detection, Line Crossing, Scenery Change, Blur Detection, Auto Tracking, Removed object, Abandoned object
Smart Intrusion Prevention	Available at 8 channels
External Backup	USB / HDD USB memory
Internal memory	2 SATA HDD 3.5" of up to 10 TB (not included)
Communication	1 x USB 3.0 / 1 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	EZStation Web Browser, Smartphone App and PC Software
Power	AC 100~240 V, 50/60 Hz
Dimensions / Weight	53 (H) x 380 (W) x 315 (D) mm / 2.6 Kg